SAFETY DATA SHEET

1. Identification

Product number Product identifier	1000008447 19 OZ OSCEOLA DSNFCTNT FM CLN LB 12PK
Company information	OSCEOLA SUPPLY INC PO Box 13503 Tallahassee, FL 32317 United States
Company phone	General Assistance 1-800-562-0292
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	01
Recommended use	DISINFECTANT
Recommended restrictions	None known.

2. Hazard(s) identification

Physical hazards

OSHA defined hazards

Health hazards

Label elements

Flammable aerosols	Category 1
Serious eye damage/eye irritation	Category 2
Not classified.	



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Causes serious eye irritation.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye protection/face protection.
Response	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.
Disposal azard(s) not otherwise assified (HNOC)	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of waste and residues in accordance with local authority requirements. None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Butoxyethanol		111-76-2	2.5 - 10
Butane		106-97-8	1 - 2.5
EDTA Tetrasodium Salt		64-02-8	1 - 2.5
Isopropyl Alcohol		67-63-0	1 - 2.5
Propane		74-98-6	0.1 - 1
Other components below reportable	e levels		80 - 90

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Not available.
	Skin contact Eye contact Ingestion Most important symptoms/effects, acute and delayed Indication of immediate medical attention and special treatment needed General information 5. Fire-fighting measures

Suitable extiliguisining media	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3
		50 ppm
Isopropyl Alcohol (CAS 67-63-0)	PEL	980 mg/m3
,		400 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
US. ACGIH Threshold Li	mit Values	
Components	Туре	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
US. NIOSH: Pocket Guid	le to Chemical Hazards	
Components	Туре	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3
		5 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	1225 mg/m3
		500 ppm
	TWA	980 mg/m3
		400 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
ogical limit values		
ogioai illilli valaoo		
ACGIH Biological Expos	sure Indices	

2-Butoxyethanol (CAS	200 mg/g	Butoxyacetic	Creatinine in	*
111-76-2)		acid (BAA), with hydrolysis	urine	
Isopropyl Alcohol (CAS	40 mg/l	Acetone	Urine	*
67-63-0)	0			

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

US - Minnesota Haz Subs: Skin designation applies 2-Butoxyethanol (CAS 111-76-2)

US - Tennessee OELs: Skin designation 2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

Skin designation applies.

Can be absorbed through the skin.

US NIOSH Pocket Guide to	Chemical Hazards: Sk	n designation		
2-Butoxyethanol (CAS 1 US. OSHA Table Z-1 Limits	,	Can be absorbed through the skin. 29 CFR 1910.1000)		
2-Butoxyethanol (CAS 1	11-76-2)	Can be absorbed through the skin.		
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.			
Individual protection measures	, such as personal prot	ective equipment		
Eye/face protection	Wear safety glasses v	Wear safety glasses with side shields (or goggles).		
Skin protection				
Hand protection	Wear appropriate che supplier.	mical resistant gloves. Suitable gloves can be recommended by the glove		
Other	Wear suitable protect	ve clothing.		
Respiratory protection	If permissible levels a air-supplied respirator	re exceeded use NIOSH mechanical filter / organic vapor cartridge or an .		
Thermal hazards	Wear appropriate the	mal protective clothing, when necessary.		
General hygiene considerations	after handling the mat	noke. Always observe good personal hygiene measures, such as washing erial and before eating, drinking, and/or smoking. Routinely wash work e equipment to remove contaminants.		

9. Physical and chemical properties

Appearance		
Physical state	Gas.	
Form	Aerosol.	
Color	Not available.	
Odor	Not available.	
Odor threshold	Not available.	
рН	Not available.	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	212 °F (100 °C) estimated	
Flash point	-156.0 °F (-104.4 °C) PROPELLANT estimated	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	
Vapor pressure	Not available.	
Vapor density	Not available.	
Relative density	Not available.	
Solubility(ies)		
Solubility (water)	Not available.	
Partition coefficient (n-octanol/water)	Not available.	
Auto-ignition temperature	446 °F (230 °C) estimated	
Decomposition temperature	Not available.	
Viscosity	Not available.	

Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.922 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.		
Skin contact	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.		
Eye contact	Causes serious eye irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.		

Information on toxicological effects

Acute toxicity		
Components	Species	Test Results
2-Butoxyethanol (CAS 111-	76-2)	
<u>Acute</u>		
Dermal		
LD50	Guinea pig	7.3 ml/kg, 4 Days
		0.23 ml/kg, 24 Hours
	Rabbit	435 mg/kg, 24 Hours
		0.68 ml/kg, 24 Hours
		0.63 ml/kg
	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rabbit	400 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
Oral		
LD100	Rabbit	695 mg/kg
LD50	Dog	> 695 mg/kg
	Guinea pig	1414 mg/kg
	Mouse	1519 mg/kg
	Rat	1746 mg/kg
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes

DTA Tetrasodium Salt (CAS 64-0 <u>Acute</u> Oral LD50 sopropyl Alcohol (CAS 67-63-0)	Rat 2-8)	1355 mg/l	
Acute Oral LD50	2-8)		
Oral LD50			
LD50			
opropyl Alcohol (CAS 67-63-0)	Rat	1658 mg/kg	
Acute			
Dermal			
LD50	Rabbit	16.4 ml/kg, 24 Hours	
Inhalation			
LC50	Rat	> 10000 ppm, 6 Hours	
Oral			
LD50	Rat	5.84 g/kg	
Propane (CAS 74-98-6)			
Acute			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
		658 mg/l/4h	
* Estimates for product may be	e based on additional component data no	ot shown.	
kin corrosion/irritation	Prolonged skin contact may cause tem	porary irritation.	
erious eye damage/eye rritation	Causes serious eye irritation.		
Respiratory or skin sensitization	l de la construcción de la constru		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause s	kin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
arcinogenicity	This product is not considered to be a c	carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall I	Evaluation of Carcinogenicity		
2-Butoxyethanol (CAS 11 OSHA Specifically Regulate	1-76-2) 3 Not cl d Substances (29 CFR 1910.1001-1050	lassifiable as to carcinogenicity to humans.)	
Not regulated.			
	gram (NTP) Report on Carcinogens		
Not listed.	T 1 1		
Reproductive toxicity	This product is not expected to cause re	eproductive or developmental effects.	
pecific target organ toxicity - ingle exposure	Not classified.		
pecific target organ toxicity - epeated exposure	Not classified.		
spiration hazard	Not likely, due to the form of the produc	ot.	
Chronic effects	May be harmful if absorbed through ski	n.	
	2-Butoxy ethanol may be absorbed throp prolonged. These effects have not bee	bugh the skin in toxic amounts if contact is repeated and on observed in humans.	

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
2-Butoxyethanol (CAS	111-76-2)		
Aquatic			
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
EDTA Tetrasodium Sa	lt (CAS 64-02-8)		
Aquatic			
Algae	IC50	Algae	1.01 mg/L, 72 Hours
Fish	LC50	Bluegill (Lepomis macrochirus)	472 - 500 mg/l, 96 hours
Isopropyl Alcohol (CAS	67-63-0)		
Aquatic			
Algae	IC50	Algae	1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-o	ctanol / water (log Kow)		
2-Butoxyethanol	0.83		
Butane	2.89		
Isopropyl Alcohol	0.05		
Propane	2.36		
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.		
Local disposal regulations	Dispose in accordance with all applicable regulations.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.		

14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
This product meets the exception	on requirements of section 173 306 as a limited quantity and may be shinned as

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

ΙΑΤΑ		
ι	JN number	UN1950
ι	JN proper shipping name	Aerosols, flammable
Т	ransport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
F	Packing group	Not applicable.
E	Environmental hazards	No.
_	RG Code	10L
S	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
C	Other information	
	Passenger and cargo	Allowed with restrictions.
	aircraft	
	Cargo aircraft only	Allowed with restrictions.
	Packaging Exceptions	LTD QTY
IMDG	ì	
ι	JN number	UN1950
ι	JN proper shipping name	AEROSOLS
Т	ransport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
F	Packing group	Not applicable.
E	Environmental hazards	
	Marine pollutant	No.
-	EmS	F-D, S-U
S	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Packaging Exceptions	LTD QTY
Anne	sport in bulk according to x II of MARPOL 73/78 and 3C Code	Not applicable.
DOT		



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Not listed. SARA 304 Emergency releations Not regulated. OSHA Specifically Regulated Not regulated. Superfund Amendments and Ref Hazard categories SARA 302 Extremely hazar Not listed. SARA 311/312 Hazardous chemical SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Other federal regulations Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) FIFRA Information US state regulations	ed Substances (29 CFR 1 eauthorization Act of 198 Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No	6 (SARA)		
OSHA Specifically Regulate Not regulated. Superfund Amendments and Re Hazard categories SARA 302 Extremely hazar Not listed. SARA 311/312 Hazardous chemical SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Other federal regulations Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) FIFRA Information	eauthorization Act of 198 Immediate Hazard - Ye Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No	6 (SARA)		
Superfund Amendments and Re Hazard categories SARA 302 Extremely hazar Not listed. SARA 311/312 Hazardous chemical SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Other federal regulations Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) FIFRA Information	Immediate Hazard - Ye Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No			
SARA 302 Extremely hazar Not listed. SARA 311/312 Hazardous chemical SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Other federal regulations Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) FIFRA Information	Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No	5		
Not listed. SARA 311/312 Hazardous chemical SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Other federal regulations Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) FIFRA Information US state regulations				
chemical SARA 313 (TRI reporting) Chemical name 2-Butoxyethanol Other federal regulations Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) FIFRA Information	dous substance			
Chemical name 2-Butoxyethanol Other federal regulations Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) FIFRA Information	No			
2-Butoxyethanol Other federal regulations Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) FIFRA Information		040	0/ have a	
Other federal regulations Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) FIFRA Information		CAS number 111-76-2	<u>% by wt.</u> 2.5 - 10	
Clean Air Act (CAA) Section Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) FIFRA Information		111-70-2	2.5 - 10	
Not regulated. Clean Air Act (CAA) Section Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) FIFRA Information	n 112 Hazardous Air Poll	utants (HΔPs) I ist		
Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act (SDWA) FIFRA Information			68.130)	
(SDWA) FIFRA Information US state regulations		(,	
US state regulations	Not regulated.			
-	Agency and is subject to requirements differ from sheets (SDS), and for w	o certain labeling require the classification criteria	by the United States Environments under federal pesti a and hazard information resticide chemicals. The privations for use	icide law. These required for safety data
-				
US. California Controlled S	ubstances. CA Departme	ent of Justice (Californi	a Health and Safety Cod	le Section 11100)
Not listed.				
US. California. Candidate C (a))		sumer Products Regul	ations (Cal. Code Regs,	tit. 22, 69502.3, subd.
2-Butoxyethanol (CAS 1 Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 6	,			
US. Massachusetts RTK - S				
2-Butoxyethanol (CAS 1 Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 6				
Propane (CAS 74-98-6)	07-00-0)			
US. New Jersey Worker and		now Act		
2-Butoxyethanol (CAS 1 Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 6	,			
Propane (CAS 74-98-6)		K		
US. Pennsylvania Worker a 2-Butoxyethanol (CAS 1		Know Law		
Butane (CAS 106-97-8) Isopropyl Alcohol (CAS 6				
Propane (CAS 74-98-6) US. Rhode Island RTK				
Butane (CAS 106-97-8)				
Isopropyl Alcohol (CAS 6 Propane (CAS 74-98-6)	67-63-0)			
Product name: 19 OZ OSCEOLA DS				

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Dimethylnitrosoamine (CAS 62-75-9) Listed: October 1, 1987

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

United States & Puerto Rico I oxic Substances Control Act (ISCA) Inventory Ye *A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

16. Other information, including date of preparation or last revision

Issue date	04-24-2017
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names